



TT-SS23L

Small Table Top Steam Sterilizer

Sterilization with LCD Touch Screen and Open Water Tank

To meet the daily needs for dental, eye, laboratory and pet medical clinics!



Front view of the unit with the LCD touch screen control panel on top

Key Features

- Rapid sterilization function
- Less water required
- Better drying effect
- Food-grade stainless steel tank and bracket
- Large LCD display panel
- Water tank with filtration function
- Built-in printer



Product Advantages



EFFICIENT STERILIZATION



STAINLESS STEEL MATERIAL



STABLE OPERATION



TEMPERATURE CONTROL



The unit with the door open: stainless steel chamber with instrument trays

Built-in Printer

Built-in printer function to clearly record experimental data.



The built-in printer unit

Large LCD Display Panel

Large screen LCD display panel and touch keys make the operation process much easier.



Control panel: pressure (kPa), temperature (°C) and time (min) readouts on the left, program and test function keys with the cycle curve and the date/time display in the center, navigation and start keys on the right

Specification

Technical parameters of the TT-SS23L model (23 L chamber):

Model	TT-SS23L
Quality Standard	Class B
Chamber (Diameter × Depth)	250 × 450 mm
External Dimension (W × D × H)	680 × 430 × 450 mm
Package Weight	57 kg
Package Size	73 × 50 × 54 cm
Rating	2200 W
Rated Voltage	110/220 V, 50/60 Hz, B
Sterilization (Pressure / Temperature)	90–130 kPa / 121 °C; 200–230 kPa / 134 °C
Tank Capacity	3.5 L
Water Capacity	0.2–0.3 L



Contact

TooToo Meditech Co., Ltd.

Address: 3A, Phase II, Smart Home, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Tel: +86-755-28306385

Email: info@newtootoo.com

Web: www.newtootoo.com